



WALLBOX POWER2CAR **FUEL**

THE SPIRIT OF THE PAST THE TECHNOLOGY TURE

www.renzwallbox.com wallbox@renz.com



POWER2CAR - FUEL

You have decided in favor of e-mobility? You are now looking for a suitable charging station for your electric vehicle? It should be special, charges fast and safely and at the same time looks really good? Then our POWER2CAR FUEL wallbox will convince you!

With the POWER2CAR FUEL, you combine the spirit of the past with the technology of the future! The robust, durable and above all unique charging station is individually produced in our manufactory. It guarantees you a future-proof technology: developed and manufactured in Germany.

We will be happy to support professional installation and offer you a comprehensive service.







The integrated bright multi-color LED always shows you the current status of the charging system.



The RFID versions enable you to release the charge with the enclosed RFID transponders (3 pieces) directly on the charging plug.

As soon as your electric vehicle is connected to the wallbox via the charging cable, hold your transponder in front of the RFID reader. The release is issued and you're ready to go.

WALLBOX CABLE HOLDER







PREMIUM HOOK

НООК

Steel, powder coated, anthracite, for wall mounting,

incl. mounting material Art.No. 4798001105

Stainless steel, brushed, silver, mounting on wall or stand possible, incl. mounting material Art.No. 4798001110

» 3.7-11 kW charging power (max. 16A)

- » DC residual current detection
- » Type 2 charging cable (5 m or 7 m)
- » Retro design steel case
- » Suitable for indoor and outdoor installation*
- » easy to operate
- » craftsman-friendly design for convenient installation
- » handmade in Germany
- in the version RFID:
 charge release through RFID technology

*Mount in a rain-protected place outdoors

POWER2CAR **FUEL**

Art.No.	olive 4798001020 pitch black 4798001021
Electrical Output:	3,7 - 11 kW (max. 16 A) DC residual current detection
Plug type:	Typ 2 (Vehicles in Europe) Lademode 3, IEC 62196
oading cable:	5 m
Electrical connection:	3 Ph, 400 V, 50/60 Hz, 16 A
Ambient temperature:	-30°C – 50°C
Housing:	Stahl (pulverbeschichtet)
Size (W/H/D):	345 x 468 x 220 mm

POWER2CAR FUEL | RFID

Н

rt.No.	olive 4798001025
	pitch black 4798001026
	platin 4798001022
	amber 4798001023
lectrical Output:	3,7 - 11 kW (max. 16 A)
	DC residual current detection
ccess protection:	RFID (Inclusive 3 RFID-Transponder)
lug type:	Typ 2 (Vehicles in Europe) Lademode 3, IEC 62196, integrated RFI
oading cable:	7 m
lectrical connection:	3 Ph, 400 V, 50/60 Hz, 16 A
mbient temperature:	-30°C – 50°C
lousing:	Stahl (pulverbeschichtet)
ize (W/H/D):	345 x 468 x 220 mm

www.renzwallbox.com wallbox@renz.com

grated RFID-Sensor